

WITA go.future 2 – 40 | 60 LCD

Product specials

- 5 Years Warranty
- Night Mode / Min. operation level
- LCD consumption display
- Venting function
- Keylock
- Anti-block function
- also available as PWM and 0 - 10 V version



Technical data

Max. pump lift	4,0 m 6,0 m
Max. flow rate	2.800 l/h 3.600 l/h
Power consumption	3 - 23 W 3 - 41 W
Control	4 constant characteristics, 4 proportional characteristics, 4 constant pressure characteristics
Additional function	minimal operation function / manually night mode, automatically night mode, LCD consumption display, venting function, keylock, anti-block function
Supply voltage	1 x 230V, 50 Hz
Motor protection	no external motor protection required
Ip rating	IP 42
Ambient temperature	0 °C to +40 °C
Media temperature	+5 °C to +110 °C
Max. system pressure	10 bar
Connection size	DN 15, DN 20, DN 25, DN 32
Installation lengths	110 mm, 130 mm, 180 mm
Pump housing material	130 mm, 180 mm variant in grey cast iron cataphoresis coated; 110 mm, 130 mm variant in brass
Weight incl. insulation	2.5 kg
EEI	≤ 0,20
Special equipment	Also available as PWM or 0-10 V version

